



# BIPV Module

EL-60/5M-B150(150 Watt)

EL-72/5M-B180(180 Watt)



## Everlight BIPV Modules

Everlight Building Integrated Photovoltaic (BIPV) modules are the best way to incorporate solar power into your building plan. Everlight BIPV modules blend into your structure in an aesthetically pleasing way, replacing conventional building materials with energy generating modules that will power your structure and save money for years to come. Additionally, you can take pride in the fact that you are drastically reducing the carbon footprint of your structure, an important consideration as governments move towards more environmentally proactive policies.

## KEY FEATURES

### Superior Performance

- Made with high quality monocrystalline solar cells to ensure output stability and industry leading power generation
- Cell conversion efficiency > 15%
- Integrated BIPV designs enhance the aesthetic qualities
- Significant reduction in carbon footprint

### Durability

- High quality, impact resistant tempered glass encapsulation protects the cells from wind, rain, snow and ice.

### Value

- One of the most cost effective ways of integrating solar power
- BIPV system costs offset by reduced costs from conventional materials and labor
- Reduced buy-back time

### Versatility

- Can be applied to a number of building components such as walls, rooftops, awnings, skylights, overhangs, slopes and windows.

### Reliability

- Manufactured to the highest standards in our ISO 9001:2008 certified plant, Helios Photovoltaic Co. Ltd.
- 25 year limited warranty on power output
- 7 year limited warranty on materials and workmanship

#### Headquarters-Hong Kong

Everlight Corporation Ltd.

2506, West Tower, Shun Tak Centre, 168-200 Connaught Road, Central, Hong Kong

Tel: +852 6614 4916 Fax: +852 2815 1975

URL: [www.everlight-solar.com](http://www.everlight-solar.com)



#### Manufacture-China

Helios Photovoltaic Co., Ltd.

Unit 3-A, 86 West Wujin Avenue, Wujin Hi-tech Industrial Zone 213164, Changzhou, Jiangsu Province, China

Tel: +86 519 8648 8901/2/3 Fax: +86 519 8648 2889

URL: [www.helios-pv.com](http://www.helios-pv.com)


## Module Specifications

ELECTRICAL CHARACTERISTICS		
Model	EL-60/5M-B	EL-72/5M-B
Maximum power (Pmax)	150 W	180 W
Voltage at max. power (Vmp)	29.8 V	35.8 V
Current at max. power (Imp)	5.033 A	5.028 A
Open circuit voltage (Voc)	36.4 V	42.8 V
Short circuit current (Isc)	5.501 A	5.614 A
Temperature coefficient of Isc		0.065%/oC
Temperature coefficient of Voc		-160mV/oC
Temperature coefficient of power		-0.45%/oC
Peak Power per Unit Area	123 W/m <sup>2</sup>	125 W/m <sup>2</sup>
CEC PTC Rating	132 W	158 W

MECHANICAL CHARACTERISTICS		
Solar Cells	60×monocrystalline 125×125	72×monocrystalline 125×125
Dimensions	1404 × 870 mm	1659 × 870 mm
Weight	28Kg	35Kg
Matrix	6×10	6×12
Solar glass	4 mm	5 mm
Thickness	9 mm	11 mm

## MODULE DIAGRAM




Electrical Performance

Power Output

Electrical Performance

Power Output



TEMPERATURE COEFFICIENTS: Isc = +0.065 %oC , Voc = -0.436 %oC , Pmax = +0.488 %oC

Note: Due to continuous innovation, research and production improvement, design and specifications are subject to change without notice. No rights can be derived from this product information sheet and Everlight assumes no liability whatsoever connected to or resulting from the use of any information contained herein. Kindly contact Everlight to obtain the latest product manuals before using.