



With our solar traffic sign series Everlight offers cost effective, efficient solutions for your modern traffic management needs.

Our solar traffic signs do not need connection to power generators or time consuming electrical attachment. They are also lightweight and portable, making them ideal for a variety of applications including traffic engineering, road crew and safety zone awareness, and speed regulation.

Everlight traffic signs are also very reliable. LED lighting units provide highly visible illumination and last much longer than conventional lights, reducing the need for frequent lamps changes and maintenance costs. Our traffic signs are also unaffected by utility grid failures and power blackouts, providing uninterrupted regulation of traffic.

Design Features

- Powered with high efficiency solar cells and solar energy battery
- Energy efficient LEDs provide high quality brightness
- Maintenance-free, sealed gel batteries
- Warranty for solar modules can last up to 25 years

Value and Convenience

- Easy installation, no manual operation or electrical cabling required
- Keep your installation costs and personnel to a minimum; reduce traffic delays
- Portable; ideal for areas with little or no electric grid connection
- Energy efficient LED lamps last upwards to 100,000 hours eliminating the need for frequent lamp changes

Environmentally Friendly

- Solar traffic signs are powered by clean, renewable and free energy from the sun.
- LED lamps are mercury free, which means no toxic waste when they are disposed
- Displaces grid supplied electricity and reduces carbon emissions

SPECIFICATIONS		
ITEM	TECHNICAL DESCRIPTION	LIFE
Work Condition	• Operating temperature: From -50°C to 70°C	
	• Operating Voltage: 12V	
	• Wind rate: 96km/h	
	• Water resistance: IP54	
	• Lighting Time: Continuous operation for 12 hours/day and up to 4 days in overcast or rainy conditions.	
Solar Panel	• 15Wp (Monocrystalline/ Polycrystalline Silicon)	25 years
Light Source	• LED power: 3W	100,000 hours
	• LED brightness: 17Lux	
	• LED color temperature: 6000-7000K (Sun color)	
	• Visibility distance: 500m	
	• Flash frequency: 24±2/min	
Frame Material	• Board Size: 1800×400mm	20 years
	• Material: Stainless Steel	
Battery	• 12V 15AH	3~5 years
	• Maintenance-free Colloid	
Controller	• 12V 10A DC	3 years
	• Time and Light switch controller	

Note: Due to continuous innovation, research and production improvement, design and specifications are subject to change without notice. No rights can be derived from this product information sheet and Everlight assumes no liability whatsoever connected to or resulting from the use of any information contained herein. Kindly contact Everlight to obtain the latest product manuals before using.



Headquarters-Hong Kong
 Everlight Corporation Ltd.
 2506, West Tower, Shun Tak Centre, 168-200
 Connaught Road, Central, Hong Kong
 Tel: +852 6614 4916 Fax: +852 2815 1975
 URL: www.everlight-solar.com



Manufacture-China
 Helios Photovoltaic Co., Ltd.
 Unit 3-A, 86 West Wujin Avenue, Wujin Hi-tech Industrial
 Zone 213164, Changzhou, Jiangsu Province, China
 Tel: +86 519 8648 8901/2/3 Fax: +86 519 8648 2889
 URL: www.helios-pv.com